



STI (HONG KONG) LIMITED

Flat 2C, 30 Johnston Road, Wanchai, Hong Kong

Tel: (852) 31162689

Fax: (852) 31162690

Shanghai Factory: Block 2, F5A, 499 Kang Yi Road, Pu Dong, Shanghai, China 201315

SAFETY DATA SHEET SECONDARY NICKEL-METAL HYDRIDE SEALED CELLS

Date issue: August 10th, 2007 Version: USA

The information contained within is provided as a service to our customers and for their information only. The information and recommendations set forth herein are made in good faith and are believed to be accurate at the date compiled. STI makes no warranty expressed or implied.

1. IDENTIFICATION

1.1 Product

Sealed secondary (or rechargeable) Cells

Trade name and model: STI...according model

IEC designation: KR... according international standard IEC 61951-1

Electrochemical system: Nickel/Metal hydride, alkaline electrolyte

Positive electrode: Nickel hydroxide

Negative electrode: Metal hydride

Electrolyte: Potassium, Sodium and Lithium hydroxide in water solution.

Nominal Voltage: 1.2Volts

1.2 Supplier

Name: SHANGHAI SUPREME TECHNOLOGIES INDUSTRIAL LTD.

Address: BLOCK2, F5A, 499 KANGYI ROAD, KANG QIAO AREA, SHANGHAI.

Tel/Fax: 86-21-68193513 / 86-21-68192594

Emergency Contact: STI local dealer

2. COMPOSITION (Weight percentage of basic materials)

Single cell with steel container

Metals (%)	Plastics (%)	Others (%)
Iron Fe 15-30	Polyamide PA/PP 2.5-3.5	Potassium K/Na/Li 1.8-3.2
Nickel Ni 30-45	Rubber EPDM <0.05	Water H2O 4-9
Rare Earth, Mn, Al 7-15	Polyethylene PE 0.2-0.4	OH- 8-14
Cobalt Co 1-5	PVC 0.2-0.7	

3. HAZARDS

A- Human hazards

A sealed Nickel-Metal hydride cell is not hazardous in normal use.

3.1 Physical

Nickel plated steel can do not present any risk of cells are used for its intended purpose and according to valid directions for use.

3.2 Chemical

Nickel plated steel cannot present chemical risk in normal use.

In case of misuse (abusive over charge, reverse charge,, external short circuit...) and in case of default, some electrolyte can leak from the cell through the safety vent.

In these cases refer to the risk of the alkaline hydroxides.

The toxic properties of the electrode materials are hazardous only if the materials are released by mechanical damaging the cell or if exposed to fire.

Classification of dangerous substances contained into the cells.

SUBSTANCES			CLASSIFICATION			
Name	EEC Number CAS Number	Symbol	Letter	Identification of danger	Special risk (1)	Safety Advice (2)
Nickel Hydroxide	028-008-x 12054-48-7	Ni(OH) ₂	Xn	Harmful	R20/22-43-40	S22/36
Cobalt Hydroxide	- 2141-93-0	Co(OH) ₂	Xn	Harmful	R22-42/43	S22-24-37
Alkaline hydroxide	019-002-00-8 1310-58-3	KOH NaOH LiOH	C	Corrosive	R35	S26-37/39 -45

(1) Nature of special risk

R 20/22: Harmful by inhalation or if swallowed.

R35: Causes serious burns.

R40: Possible risk of irreversible effects.

R43: May cause sensitizing by skin contact.

R42/43: May cause sensitizing by inhalation and skin contact.

(2) Safety advice

S22: Do not breathe dust.

S24: Avoid contact with skin

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36: Wear suitable protection clothing.

S37: Wear suitable protection gloves.

S37/39: Wear suitable gloves and eyes/face protection.

S45: In case of accident or of you feel unwell, seek medical advice immediately.

B- Ecological hazards

Metals used in a Ni-MH cell have to be collected and recycled.

4. FIRST AID MEASURES

In case of electrolyte solution spill (cell leakage) precautions must be taken to avoid any contact of human tissues. If it accidentally happens following must be done:

4.1 Inhalation

Fresh air. Rinse mouth and nose with water. Medical treatment.

4.2 Skin contact

Rinse immediately with plenty of water. Medical treatment.

4.3 Eyes contact

Rinse immediately with plenty of water during at least 15-30 min. Immediate hospital treatment. Consult eye specialist.

4.4 Ingestion

If the injured is fully conscious: plenty of drink, preferably milk. Do not induce vomiting. Immediate Hospital treatment.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Suitable: Class D-Dry chemical, sand, CO₂.

Not to be used: Water.

5.2 Special exposure hazards

Cells can be overheated by an external source or by internal shorting and release alkaline electrolyte mist or liquid. Electrolyte reacts with zinc, aluminum, tin and other active materials releasing flammable hydrogen gas.

In case of PVC sleeved products, the combustion releases chloride gas.

5.3 Special protective equipment

Use self-contained breathing apparatus and full fire-fighting protective clothing.

6. SPILL MANAGEMENT PROCEDURE

The sealed Ni-MH cells when sleeved are safe in case of spilling.

Non-sleeved cells may generate short-circuits, causing release of alkaline electrolyte mist or liquid. Electrolyte reacts with zinc, aluminum, tin and other active materials releasing flammable hydrogen gas. In such a case, use self-contained breathing apparatus and protective clothing.

7. HANDLING AND STORAGE

In normal use conditions, no safety rule is specified to handle the cells.

It is recommended to store following STI specifications in order to ensure longer usage: +5 to +25⁰C in a 65+-5% relative humidity.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Under normal condition of use and handling no special protection is required for sealed Ni-MH cells.

9. PHYSICAL PROPERTIES

9.1 Appearance

Nickel plated steel cylindrical cell, eventually sleeved. Dimensions and color according

specification.

9.2 Temperature range

Risk of electrolyte leakage over 100°C

9.3 Specific energy

35 to 80 Wh/Kg

9.4 Specific instant power

Up to 1000 W/Kg during 1 second

9.5 Mechanical resistance

According mechanical tests in IEC 61951-2 standard.

10. STABILITY AND REACTIVITY

10.1 Conditions

Ni-MH cells are stable in storage.

In case of storage in Humidity, some rust may appear on the product.

In case of storage in a charged state, cells progressively loose their energy, generating eventually a progressive temperature increase according the thermal insulation efficiency of the packaging.

In case of exposure to temperature over 100°C, a risk of release of alkaline electrolyte mist or liquid is created. A higher temperature (160°C) the plastics used can melt or decompose (Polyamide gasket, rubber valve, PVC sleeve,...).

In case of mechanical deterioration of the cells, active materials contained as powder can be dispersed (Nickel, Cobalt, metal hydride).

10.2 Hazardous decomposition products

Electrolyte solution is corrosive to all human tissues and will react violently with many organic chemicals.

Electrolyte solution reacts with zinc, aluminum, tin and other materials releasing flammable hydrogen gas.

11. TOXICOLOGICAL INFORMATION

SUBSTANCES			HAZARDS		
Name	N° EEC N° CAS	Symbol	Effects	Dust exposure limits	Carcinogenicity
Nickel Hydroxide	028-008-X* 12054-48-7	Ni(OH)2	LD50/oral/rat: 1600 mg/Kg	VME : 1000µg/m3 VLE:/	Occupational
Hydroxide de cobalt	- 21041-93-0	Co(OH)2	LD50.Not available	VME : 100µg/m3 VLE:/	/
Alkaline Hydroxides	019-002-00-8 1310-58-3	KOH NaOH LiOH	LD50/oral/rat: 365mg/Kg	KOH VME:2mg/m3 NaOH VME:2mg/m3 LiOH VME:25µg/m3	/

12. ECOLOGICAL INFORMATION

The storage battery is TCLP toxic. If not recycled, must be disposed of in accordance with all state and local regulations.

13. DISPOSAL CONSIDERATIONS

13.1 Incineration

Never incinerate Ni-MH batteries.

13.2 Landfill

Never dispose Ni-MH batteries as landfill.

13.3 Recycling

Nickel Metal hydride batteries can be fully recyclable. They are submitted to the **European community directive 91-157/CE**. STI recommends proper recycling of these batteries whenever possible.

You may refer to the following web page for further information and guidance:

www.ocde.org/ehs.htm *. You can also contact STI.

* This page provides links to different National Battery Associations and National Collection & Recycling Organizations that can provide you with the latest update on collection & recycling in their respective Countries.

14. TRANSPORT INFORMATION

Sealed Ni-MH batteries with sleeve are not submitted to specific transport obligations. Sealed Ni-MH batteries without sleeve are submitted to ADR prescription under UNO code 2800.

15. REGULATORY INFORMATIONS

Nickel Metal hydride batteries are submitted to the European community directive 91-157/CE for recycling.

16. OTHER INFORMATIONS

Consult STI specifications and precautions of use for optimized use.